

MISCELLANEOUS HARDWARE



Cleats

- Strong aluminum anodized cleats :
- three sizes : lg 120, lg 160, lg 200 mm.



Electrical insulations

- Our PVC insulation fits onto the mast section groove. It makes it easier for the electrical wire to go through, and guarantees phonic isolation with the halyards. Available in Ø25 and Ø32 (length 3000mm)).



Mast climbing steps



Composite steps

- The climbing steps allow rapid intervention either on all the length of the mast, or part of it (one or two to easily grab the main sail head for example).
 - Two types: fixed stainless steel, or nylon folding steps (white or grey).
- Warning : before using the steps, one must be belayed and secure the handling.



Stainless steel steps

Sail gates, sail entries

- Automatic or simple sail gates: they keep the main sail slider in the sailtrack.
- Bolt rope feeder ø 8,
- Feeder
- Main sail slider entry key

Ball feeder



Trackless sliders



Delrin bolt rope feeder




Stainless steel pad eye

Lazy jacks fittings

- Stamped eyes, stainless steel plates or s/s moulded pad eyes (for maxi-yachts), fixed on boom for lazy jacks/bags.

Adjusters

- Body, toggle and screws are made of stainless steel.
- The frictional ring brings a good comfort in maneuvering.
- Available in standard or removable version, for wires from ø 6 to ø 8mm.



Adjusters

Models	Pin-to-pin length		body ø	use for backstay
	Mini	Maxi		
5 tons pelican hook	315	470	25	ø 6 - 7
5 tons toggle - toggle	400	605	28	ø 8
6,5 tons pelican hook	505	715	25	ø 6 - 7
6,5 tons toggle - toggle	515	710	28	ø 8