



Sparcraft offers a new range of bowsprits. Easily removed from the deck these innovative spars can be fitted on sailing boats from 25 to 57 feet. They have been specially designed for Gennakers/Code zero or asymmetric Spinnakers. The deck fixing device allows a free foredeck when arriving at the harbour or mooring.

REMOVABLE BOWSPRIT

Simple and easy functioning



Deck fixing block

- Easy fixation thanks to an automatic locking device on deck fixing blocks;



Integrated line stopper

- Simple installation (only a short backwards movement is needed to fit the bowsprit on the deck);

- Quick removal and storage on a third fixing block;
- Integrated line stopper for holding the tackline;

- The locking system incorporates an anti-theft device.

Complete kit including :

- Aluminium bowsprit with special end fittings : bridle attachment at the front and fixing block device at the back (delivered pre-installed);


- Adjustable Central fixing collar;

- Deck fixing blocks.



Ergonomic design

- End fitting has a integral machined sheave;
- Bridle attachment integrated in the front end fitting design;



- The central fixing collar is captive from the bowsprit but it is removable from the fixing block. The foredeck is therefore totally free (no more fixed collar in the way).



Technical datas

section \varnothing (mm) Alu.	Total length (mm - feet)	Minimum length inside (mm- feet)	Maximum length outside (mm)	Use example Boat length (feet)	Maximum sail area (m ²)	
					Asymmetric spinnaker	Gennaker & Code O
\varnothing 70	1600 - 5'3"	800 - 2'7"	800 - 2'7"	25-36'	60	37*
\varnothing 80	1800 - 5'10"	900 - 2'11"	900 - 2'11"	36-40'	82	52*
\varnothing 90	1900 - 6'2"	950 - 3'1"	950 - 3'1"	40-47'	102	65*
\varnothing 100	2000 - 6'6"	1000 - 3'3"	1000 - 3'3"	48-57'	130 / 150*	105*

*with briddles

THE SPARCRAFT BOWSPRIT ADVANTAGES

- Easy foredeck installation and removal;
- Automatic locking device for a maximum safety;
- Suitable for a large range of sailboats



Options

- Articulating toggle for Gennaker / Code zero furler attachment,
- Fixing plate fitted on stem-head.

