



Ref N°	Wire Ø Câble Ø mm	Thread Filetage UNF	D mm	Z mm	X mm	L0min/max mm	L1min/max mm	Break. load Charge Rupture [kg]
R1322060130	6	1/2"	12.7	39.0	14.0	294 - 374	354 - 434	4100
R1322070130	7	1/2"	12.7	38.5	14.0	294 - 374	364.5 - 444.5	5650
R1322080130	8	1/2"	12.7	38.5	14.0	296 - 376	372 - 452	5910
R1322100160	10	5/8"	15.9	40.2	17.5	359 - 505	453 - 599	8665
R1322120190	12	3/4"	19.1	54.1	21.5	432 - 604	564 - 736	11225
R1322120220	12	7/8"	22.2	69.9	24.0	510 - 627	625 - 742	17585
R1322127190	12.7	3/4"	19.1	53.5	21.5	426 - 554	546 - 674	12880
R1322140220	14	7/8"	22.2	67.0	24.0	497 - 704	653 - 860	16570
R1322160250	16	1"	25.4	64.0	28.0	530 - 686	706 - 862	21350
R1322190280	19	1" 1/8	28.0	68.0	32.0	611 - 881	821 - 1091	28105
R1322220320	22	1" 1/4	31.8	82.0	36.5	625 - 810	867 - 1052	35185

* Other dimension: contact us / Autres dimensions : nous contacter.

