



	Ø Internal cavity Cavité interne	T (mm)	h (mm)	H (mm)	Ø Furling rod Tringle	Ø Bolt rope Ralingue (mm)	Groove Gorge (mm)	d (mm)	A (mm)	Bolt rope storm sail Ralingue voile tempête			
										M (mm)	N (mm)	O (mm)	P (mm)
<b>S265E</b>	Ø90	350	40	(6%xE)+h	Ø30	Ø6	3	100	-	17,5	4,4	5	3
<b>S365E</b>	Ø90	350	40	(6%xE)+h	Ø30	Ø6	3	100	-	17,5	4,4	5	3
<b>S560E</b>	Ø100	450	30	(6%xE)+h	Ø33	Ø7	3,8	90	250	17,5	4,5	5	3,5
<b>S760E</b>	Ø115	480	50	(7%xE)+h	Ø33	Ø7	3,8	90	250	17,5	4,5	5	3,5
<b>S980E</b>	Ø115	500	50	(7%xE)+h	Ø33	Ø7	3,8	90	250	17,5	4,5	5	3,2
<b>S1420E</b>	Ø140	500	65	(7%xE)+h	Ø33	Ø7	3,8	90	250	17,5	4,5	5	3,2
<b>S1980E</b>	Ø150	550	70	(7%xE)+h	Ø33	Ø7	3,8	90	250	26	6,5	14	4,7
<b>S3800E</b>	Ø170	500	95	(7%xE)+h	Ø45	Ø6	3,5	260	250	25	5,7	14	4,7